

Infrared gas sensors: **GUARDIAN RANGE**

THE GUARDIAN[®] NG DC

FOR CO₂, CH₄ AND CO



EDINBURGH
SENSORS



KEY FEATURES

- Low Voltage DC Supply
- Concentration readings of a wide range of pressures (pressure compensated)
- Improved screen display provides more information
- Easier to set up using on-screen menus
- Digital Alarm set points
- Easier transfer of data via on board RS232 I/F
- Password protection to prevent accidental or deliberate change of settings
- Graphical display of historic readings
- Optional Ethernet I/F
- Relay outputs for control of external devices

A NEW GENERATION OF GAS SENSORS | FAST, ACCURATE AND RELIABLE

The Guardian[®] NG DC infrared gas monitor offers near-analyser quality continuous sampling, measurement and display of CO₂ concentrations between 0 – 3000ppm to 0-100% by volume from low voltage DC supplies in the range of 18-30V.

With tens of thousands of our monitors supporting critical processes in industries throughout the world we have an enviable reputation for reliability, accuracy, long-term stability plus low maintenance requirements. This can be attributed to our proprietary infrared sensor technology

Suitable for a wide variety of applications, these wall-mounted monitors can detect CO₂ from sampling points up to 30 metres away, using the integral sampling system.

Our Guardian[®] NG instruments are easy to install stand-alone products that require minimum set up. The Guardian[®] NG is supplied with LCD display and digital alarm set-point controls, housed in a robust plastic IP54 rated enclosure to prevent the ingress of particulates and water.

TECHNICAL SPECIFICATIONS

GAS MEASUREMENT RANGE

MODEL	CO ₂	CH ₄ *	CO*
Guardian NG DC	0-3000 ppm	-	-
Guardian NG DC	0-1%	-	-
Guardian NG DC	0-3%	-	0-3%
Guardian NG DC	0-5%	0-5%	-
Guardian NG DC	0-10%	0-10%	0-10%
Guardian NG DC	0-30%	0-30%	0-30%
Guardian NG DC	0-100%	0-100%	0-100%
Guardian NG DC	0-100% Biogas	0-100% Biogas	
Accuracy	±2% of full scale**		
Operating temperature	0-40°C		
Humidity	Measurements are unaffected by 0-95% relative humidity, non-condensing		
Power requirements	24V DC (18-30 V DC)		
Power consumption	13W typical (25W Max)		
Response time	T ₉₀ <30 seconds from sample inlet		
Outputs	4-20mA / 0-20mA analogue output 11V guaranteed drive capability Alarm 1 relay, Alarm 2 relay and Fault relay SPCO (single pole change-over)		
Voltage	8A at 250V AC (resistive load) 8A at 24V DC (resistive load)		
Enclosure rating	IP54		

The Guardian NG DC can also be supplied with an Ethernet option and additional accessories including CO₂ zero calibration kit and filters.

* Guardian NG DC instruments are not certified for use where risk of fire or explosion exists.

During operation prolonged exposure to high levels of flammable gases may lead to the creation of an explosive mixture within the Guardian enclosure. Additional measures must be taken by the user to prevent this hazard occurring.

** Not including calibration gas tolerance.

GUARDIAN NG DC PRODUCT APPLICATIONS:

- BIOGAS
- PERSONAL SAFETY
- PROCESS CONTROL
- IAQ
- HORTICULTURE
- BREWING
- MARINE APPLICATIONS
- And many more

For more information, contact:

Edinburgh Sensors Ltd
4 Bain Square,
Kirkton Campus,
Livingston, EH54 7DQ
United Kingdom

T: +44 (0)1506 425 300
F: +44 (0)1506 425 320

E: sales@edinst.com
W: www.edinburghsensors.com

All specifications are believed to be correct at the time of publication, Edinburgh Sensors does not accept liability for any errors or omissions. Due to our continuous product development all specifications are subject to change without prior notice.

